11.General Diagnostic Table

A: INSPECTION

Symptom or trouble	Possible cause	Remedy
1. Oil leakage	(1) Worn, scratched, or incorrectly seated front or side oil seal. Scored, battered or excessively worn sliding surface of companion flange.	Repair or replace.
	(2) Clogged or damaged air breather cap.	Clean, repair or replace.
	(3) Loose bolts on the side retainer, or incorrectly fitted O-ring.	Tighten the bolts to specified torque. Replace the O-ring.
	(4) Loose rear cover attachment bolts or damaged gasket.	Replace the gasket, and tighten the bolts to specified torque.
	(5) Loose filler plug or drain plug.	 Apply liquid gasket, and tighten to the specified torque. (T-type) Replace the gasket, and tighten to the specified torque. (VA-type)
	(6) Wear, damage or incorrect fitting of drive shaft, side retainer or oil seal.	Repair or replace.
2. Seizure	(1) Insufficient backlash for hypoid gear.	Readjust or replace.
NOTE: Seized or damaged parts should be replaced, and also other parts should be thoroughly checked for any defect and should be repaired or replaced as required.	(2) Excessive preload for side, rear or front bearing.	Readjust or replace.
	(3) Insufficient or improper oil used.	Add recommended oil to the specified level.
3. Damage	(1) Improper backlash for hypoid gear.	Readjust or replace.
NOTE: Damaged parts should be replaced, and	(2) Insufficient or excessive preload for side, rear or front bearing.	Readjust or replace.
also other parts should be thoroughly	(3) Excessive backlash for differential gear.	Replace gear or thrust washer.
checked for any defect and should be repaired or replaced as required.	(4) Loose bolts and nuts such as hypoid driven gear bolt.	Retighten.
	(5) Damage due to overloading.	Replace.
4. Noises when starting or shifting gears NOTE: Noises may be caused by differential as-	(1) Improper tooth contact of hypoid driven gear and drive pinion	Readjust. (drive pinion adjustment and backlash adjustment)
	(2) Excessive backlash for hypoid driven gear	Replace the gear or the pinion height adjusting washer.
sembly, universal joint, wheel bearing,	(3) Excessive backlash for side gear.	Replace gear or thrust washer.
etc. Find out what is actually making noise before disassembling.	(4) Insufficient preload for front or rear bearing.	Readjust.
	(5) Loose drive pinion nut.	Tighten to the specified torque.
	(6) Loose bolts and nuts such as side retainer attachment bolt.	Tighten to the specified torque.
5. Noises when cornering	(1) Damaged differential gear.	Replace.
	(2) Excessive wear or damage of thrust washer.	Replace.
	(3) Broken pinion mate shaft.	Replace.
	(4) Stuck or damaged side bearing	Replace.

General Diagnostic Table

DIFFERENTIALS

Symptom or trouble	Possible cause	Remedy
6. Gear Noise NOTE:	(1) Improper tooth contact of hypoid driven gear and drive pinion	Readjust or replace the hypoid gear set.
Since noises from engine, muffler, transmission, propeller shaft, wheel bearings,	(2) Improper backlash of the hypoid driven gear	Readjust.
tires, and body are sometimes mistaken	(3) Scored or chipped teeth of hypoid gear.	Replace hypoid gear set.
for noises from differential assembly, be careful in checking them. Inspection	(4) Scuffed hypoid gear	Replace hypoid gear set.
methods to locate noises include coast-	(5) Improper preload for front or rear bearings.	Readjust.
ing, accelerating, cruising, and lifting-up all four wheels. Perform these inspec-	(6) Stuck, scored or chipped teeth of front or rear bearing	Replace.
tions according to the condition of trouble. When listening to noises, shift the	(7) Stuck, scored or chipped teeth of side bearing	Replace.
gear into four-wheel drive and fourth speed position, trying to pick up only differential noise.	(8) Vibrating differential gear.	Replace the differential gear.

TRANSFER CASE

TC

		Page
1.	General Description	
	Transfer Case and Extension Case Assembly	
	Transfer Clutch	
4.	Extension Case	5
	Oil Seal	
6.	Transfer Drive Gear	7
7.	Transfer Driven Gear	8
8.	Reduction Drive Gear	g
	Reduction Driven Gear	
0.	Center Differential	11
1.	Transfer Clutch Pressure Test	12